



## 6.5 Creedmoor

.264"	6.5mm GD
Weight (grains)	140
Ballistic Coefficient	0.571
Sectional Density	0.287
COAL Tested	2.700"
Speer Part No.	264140GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Hornady	CCI 200	42.4	2582	46.9 C	2855
Alliant Power Pro 4000-MR	Hornady	CCI 200	40.1	2555	44.6 C	2804
Alliant Reloder 19	Hornady	CCI 200	42.1	2538	46.5 C	2801
Alliant Reloder 23	Hornady	CCI 200	41.3	2570	45.7 C	2794
Alliant Reloder 16	Hornady	CCI 200	38.6	2543	42.9 C	2790
Alliant Reloder 17	Hornady	CCI 200	37.2	2487	41.3	2769
Accurate 4350	Hornady	CCI 200	39.0	2505	43.3 C	2754
Hodgdon H4350	Hornady	CCI 200	37.9	2497	42.0	2737
Hodgdon Hybrid 100V	Hornady	CCI 200	36.9	2491	40.8	2726
Hodgdon H414	Hornady	CCI 200	37.3	2504	41.4	2724
Alliant Power Pro 2000-MR	Hornady	CCI 200	36.3	2483	40.3	2720
Vihtavuori N550	Hornady	CCI 200	35.9	2458	39.9	2716
IMR 4831	Hornady	CCI 200	38.9	2414	43.1 C	2679
IMR 4451	Hornady	CCI 200	37.1	2420	41.2	2658

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load