



6.5 Creedmoor

.264"	6.5mm
Weight (grains)	Spitzer SP Hot-Cor®
Ballistic Coefficient	140
Sectional Density	0.498
COAL Tested	0.287
Speer Part No.	2.760"
	1441

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 23	Hornady	CCI 200	40.9	2553	45.4 C	2779
Alliant Reloder 19	Hornady	CCI 200	40.1	2537	44.5	2775
Alliant Power Pro 4000-MR	Hornady	CCI 200	40.2	2534	44.6	2771
Alliant Reloder 17	Hornady	CCI 200	37.4	2494	41.5	2747
Alliant Reloder 16	Hornady	CCI 200	38.0	2546	42.0	2746
IMR 4831	Hornady	CCI 200	38.9	2523	42.7	2731
Hodgdon Hybrid 100V	Hornady	CCI 200	37.2	2492	41.2	2719
Hodgdon 414	Hornady	CCI 200	37.2	2487	41.3	2710
Accurate 4350	Hornady	CCI 200	39.5	2550	42.5	2697
Hodgdon 4350	Hornady	CCI 200	36.7	2488	40.5	2678
Alliant Reloder 15	Hornady	CCI 200	34.6	2456	38.1	2651
IMR 4451	Hornady	CCI 200	37.4	2398	41.4	2638
Alliant Power Pro 2000-MR	Hornady	CCI 200	34.5	2458	37.9	2629
Hodgdon Varget	Hornady	CCI 200	33.4	2425	37.0	2615
IMR 4064	Hornady	CCI 200	33.0	2397	36.5	2602
Alliant Power Pro Varmint	Hornady	CCI 200	32.7	2388	36.2	2595
Vihtavouri N150	Hornady	CCI 200	32.0	2326	35.6	2529
Alliant AR-Comp	Hornady	CCI 200	30.9	2358	33.6	2500

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load