

## RUGER PRECISION RIFLE™ BOLT-ACTION RIFLE



Optics Not Included

Model Number	Caliber	Capacity	Stock	Barrel	Barrel Length	Folded Length	Overall Length	Height	Width	Weight	Length of Pull	Twist	Suggested Retail
18001	308 Win	10	Folding, Adjustable Length of Pull and Comb Height	Cold Hammer-Forged, 5R Rifling	20.00"	30.60"	38.25" - 41.75"	7.30"	3.30"	9.70 lbs.	12.00"-15.50"	1:10"	\$1,399.00
18005	6.5 Creedmoor	10	Folding, Adjustable Length of Pull and Comb Height	Cold Hammer-Forged, 5R Rifling	24.00"	34.60"	42.25" - 45.75"	7.30"	3.30"	10.60 lbs.	12.00"-15.50"	1:8"	\$1,399.00
18010	243 Win	10	Folding, Adjustable Length of Pull and Comb Height	Cold Hammer-Forged, 5R Rifling	26.00"	36.60"	44.25" - 47.75"	7.30"	3.30"	11.00 lbs.	12.00"-15.50"	1:7.7"	\$1,399.00

- **Medium contour (.75" at the muzzle) barrel** features 5/8"-24 threads. Thread protector installed.
- **Highly accurate Ruger cold hammer-forged** 4140 chrome-moly steel barrel with 5R Rifling at minimum bore and groove dimensions, minimum headspace and centralized chamber.
- **Equipped with a Samson Evolution Keymod Handguard.** May be configured with any AR-style handguard.
- **20 MOA Picatinny rail secured with four, #8-40 screws** for increased long-range elevation capabilities.
- **"Upper" receiver and one-piece bolt** are precision CNC-machined from pre-hardened 4140 chrome-moly steel to minimize distortion.
- **Three-lug bolt with 70° throw** features dual cocking cams and a smooth-running, full diameter bolt body.
- **In-line recoil path manages recoil directly from the rear** of the receiver to the buttstock, not through a traditional bedding system, providing maximum accuracy potential.
- **Ruger® Precision MSR stock** with QD sling attachment points features a bottom Picatinny rail and soft rubber buttpad. The left-folding stock hinge is attached to an AR-style buffer tube and accepts any AR-style stock.
- **Barrels can be easily replaced** by a competent gunsmith using AR-style wrenches and headspace gauges.
- **Magazine well front is contoured** for a positive grip for bracing against shooting supports.

- **Oversized bolt handle for positive bolt manipulation**, with 5/16"-24 thread for easy replacement. Bolt disassembly tool is stored in the bolt shroud for easy striker channel cleaning.
- **"Lower" magazine well halves are precision machined** from aerospace-grade 7075-T6 aluminum forging and are Type III hard coat anodized for maximum durability.
- **Multi-Magazine Interface functions interchangeably** with M110, SR25, DPMS and Magpul®-style magazines and AICS magazines (works with some M-14 magazines); two 10-round Magpul® PMAG® magazines included.
- **Ruger Marksman Adjustable™ trigger** is externally adjustable with a pull weight range of 2.25 to 5.0 lbs.; wrench is stored in the bolt shroud.
- **Extended trigger-reach AR-style grip** and 45° reversible safety selector. May be configured with any AR-style grip and selector.