



BPI LOAD GUIDE:

12GA CP RIFLED LEAD SLUG

WWW.BALLISTICPRODUCTS.COM

Our VALU-SLUGS come from a major U.S. cartridge manufacturer. They are contained and sorted by size through a rigid demilitarization process*. BPI is offering these slugs in box quantities to maximize savings for our customers.

12ga Valu-Slug RRLS438 Copper-Plated Rifled Lead Slug Technical Specs:

Diameter: .730"

Height: .705"

Weight: 470 grains (approx. 1-1/16 oz.)

Type: Copper-plated rifled lead foster slug

Size: NOTE - These are approximate weights and sizes. Actual measurements may vary.

* **De-Mil materials:** This means that these components have been extracted from manufactured cartridges. The company that performs this action acknowledges that imperfections can and do exist in these components. This is why they are priced very aggressively. If you require perfect components, please look at our specific departments for newly-manufactured components.



LOAD ID	GA.	HULL	PRIMER	POWDER	POWDER GRAINS	GAS SEAL	WAD	FILLER WADS & LOAD INSERTS	PROJECTILE	OVER SHOT	SLUG WEIGHT (OUNCES)	SLUG WEIGHT (GRAINS)	PSI	FPS
12-GAUGE • 2-3/4" LENGTH • 470 GR COPPER-PLATED RIFLED LEAD SLUG • ROLL CRIMP														
230616-11885	12	Cheddite	Ched209	High Gun	26.0		BRP-12	HCW12	470 GR CP RIFLED LEAD SLUG		1-1/16 (approx.)	470	11000	1422
230616-11883	12	Cheddite	Ched209	Perfect Pattern	22.3		BRP-12	HCW12	470 GR CP RIFLED LEAD SLUG		1-1/16 (approx.)	470	9900	1302
230616-11884	12	Cheddite	Ched209	W S Handicap	30.2		BRP-12	HCW12	470 GR CP RIFLED LEAD SLUG		1-1/16 (approx.)	470	10700	1474
230616-11886	12	Federal PB	Fed209A	Perfect Pattern	22.2		BRP-12	HCW12	470 GR CP RIFLED LEAD SLUG		1-1/16 (approx.)	470	11000	1303

WARNING: ALL SLUG BARRELS ARE NOT EQUAL. SOME SLUG BARRELS ARE MADE TOO LIGHT AND TOO THIN FOR USE WITH CERTAIN SLUG OR SABOT LOADS. IF YOUR SLUG BARREL IS THIN (.040" - .060") AT THE MUZZLE OR ANYWHERE ELSE (USE A MICROMETER) WE SUGGEST YOU DO NOT USE THE BARREL. (FOR INSTANCE, A VERY STRONG MOSSBERG SLUG BARREL RECENTLY MEASURED, BOASTS .110" THICKNESS - ALMOST THREE TIMES THE THICKNESS OF IMPORTED LIGHTWEIGHT SLUG BARRELS.)

WARNING: WARNING: BALLISTIC PRODUCTS, INC. DISCLAIMS ALL POSSIBLE LIABILITY FOR DAMAGES, INCLUDING ACTUAL, INCIDENTAL, AND CONSEQUENTIAL, RESULTING FROM USAGE OF INFORMATION OR ADVICE CONTAINED IN THIS AND OTHER PUBLICATIONS, LABELS, CATALOGS, TESTING REPORTS AND BOOKLETS. USE DATA AND ADVICE AT YOUR OWN RISK AND WITH CAUTION. WHERE DATA LIST SPECIFIC COMPONENTS, NO CHANGES OR SUBSTITUTIONS FOR THESE COMPONENTS CAN BE MADE WITHOUT RISKING SIGNIFICANT CHANGES IN THE LEVEL OF BALLISTIC PERFORMANCE AND/OR SAFETY OF THE LOADS SHOWN. FOLLOW LOADING DATA EXACTLY AND DO NOT SUBSTITUTE COMPONENTS. WE MAKE NO WARRANTIES EXPRESS OR IMPLIED, LIMITED OR FULL, AND WE DISCLAIM ANY SUCH WARRANTIES. FAILURE TO COMPLY WITH THESE AND OTHER STANDARDS OF RELOADING MAY RESULT IN ACCIDENTS WITH SERIOUS INJURY AND/OR DEATH TO THE SHOOTER AND/OR BYSTANDERS. KEEP OUT OF REACH OF CHILDREN. WE DISCLAIM ANY AND ALL LIABILITY FOR DAMAGE OR INJURY THAT MAY RESULT FROM YOUR HANDLOADED SHOTSHELLS AS WE HAVE NO CONTROL OVER ANY OF THE NUMEROUS POSSIBLE VARIATIONS IN COMPONENT PRODUCTION LOTS, IN TOOL AND DIE DIMENSIONS, IN YOUR LOADING PRACTICES AND PROCEDURES. THE INDIVIDUAL RELOADER IS SOLELY RESPONSIBLE FOR ANY VARIATION THAT MAY BE INCURRED BY ASSEMBLED AMMUNITION. TO AVOID SERIOUS INJURY OR DEATH TO SHOOTER AND BYSTANDERS, THIS PRODUCT SHOULD ONLY BE USED IN GUNSMITH-INSPECTED GUNS DESIGNED FOR MODERN SHOTSHELLS. IF GUN FAILS TO FIRE, KEEP POINTED IN SAFE DIRECTION FOR 30 SECONDS, THEN UNLOAD CAREFULLY. WEAR EYE AND EAR PROTECTION AND OBSERVE PROPER GUN SAFETY AT ALL TIMES. ALL PRODUCTS SOLD "AS IS".