




Surveying - Traverse





Introduction

- Almost all surveying requires some calculations to reduce measurements into a more useful form for determining distance, earthwork volumes, land areas, etc.
- A traverse is developed by measuring the distance and angles between points that found the boundary of a site
- We will learn several different techniques to compute the area inside a traverse


Surveying - Traverse

Surveying - Traverse





Distance - Traverse




Methods of Computing Area


- A simple method that is useful for rough area estimates is a **graphical method**
- In this method, the traverse is plotted to scale on graph paper, and the number of squares inside the traverse are counted



Distance - Traverse




Methods of Computing Area




$$\text{Area } ABC = \frac{1}{2} ac \sin \alpha$$

Distance - Traverse



Methods of Computing Area




$$\text{Area } ABD = \frac{1}{2} ad \sin \alpha$$


$$\text{Area } BCD = \frac{1}{2} bc \sin \beta$$

$$\text{Area } ABCD = \text{Area } ABD + \text{Area } BCD$$

Distance - Traverse



Methods of Computing Area




$$\text{Area } ABE = \frac{1}{2}ae \sin \alpha$$

$$\text{Area } CDE = \frac{1}{2}cd \sin \beta$$

➤ To compute **Area BCD** more data is required

Surveying - Traverse




Balancing Angles


- Before the areas of a piece of land can be computed, it is necessary to have a **closed traverse**
- The **interior angles** of a **closed traverse** should total:

$$(n - 2)(180^\circ)$$
 where n is the number of sides of the traverse


Surveying - Traverse



Balancing Angles



Surveying - Traverse




Balancing Angles

- A surveying heuristic is that the total angle should not vary from the correct value by more than the square root of the number of angles measured times the precision of the instrument
- For example an eight-sided traverse using a 1' transit, the maximum error is:

$$\pm 1' \sqrt{8} = \pm 2.83' = \pm 3'$$


Surveying - Traverse



Balancing Angles


- If the angles do not close by a reasonable amount, mistakes in measuring have been made
- If an error of 1' is made, the surveyor may correct one angle by 1'
- If an error of 2' is made, the surveyor may correct two angles by 1' each
- If an error of 3' is made in a 12 sided traverse, the surveyor may correct each angle by 3'/12 or 15"

Surveying - Traverse




Latitudes and Departures

- The **closure** of a traverse is checked by computing the latitudes and departures of each of its sides




Surveying - Traverse




Latitudes and Departures

- The **latitude** of a line is its projection on the north-south meridian



- The **departure** of a line is its projection on the east-west line
- A northeasterly bearing has:
 - + latitude and
 - + departure

Surveying - Traverse




Error of Closure

- Consider the following statement:

"If start at one corner of a closed traverse and walk its lines until you return to your starting point, you will have walked as far north as you walked south and as far east as you have walked west"
- Therefore $\sum \text{latitudes} = 0$ and $\sum \text{departures} = 0$


Surveying - Traverse



Error of Closure


- When latitudes are added together, the resulting error is called the **error in latitudes (E_L)**
- The error resulting from adding departures together is called the **error in departures (E_D)**

Surveying - Traverse



Error of Closure

- If the measured bearings and distances are plotted on a sheet of paper, the figure will not close because of E_L and E_D




Error of closure

$$E_{closure} = \sqrt{(E_L)^2 + (E_D)^2}$$


Precision = $\frac{E_{closure}}{\text{perimeter}}$

Typical precision: 1/5,000 for rural land, 1/7,500 for suburban land, and 1/10,000 for urban land


Surveying - Traverse




Latitudes and Departures - Example



Surveying - Traverse



Latitudes and Departures - Example




Departure_{AB}

$$-W = -(189.53 \text{ ft.}) \sin(6'15'') = -20.63 \text{ ft.}$$


Latitude_{AB}

$$-S = -(189.53 \text{ ft.}) \cos(6'15'') = -188.40 \text{ ft.}$$

Surveying - Traverse




Latitudes and Departures - Example



Departure_{BC}


 $+E = (175.18 \text{ ft.}) \sin(29^\circ 38') = 86.62 \text{ ft.}$



Latitude_{BC}

 $-S = -(175.18 \text{ ft.}) \cos(29^\circ 38') = -152.27 \text{ ft.}$


Surveying - Traverse



Latitudes and Departures - Example

Side	Bearing			Length (ft.)	Latitude	Departure
	degree	minutes				
AB	S	6	15	W	189.53	-188.403
BC	S	29	38	E	175.18	-152.268
CD	N	81	18	W	197.78	29.916
DE	N	12	24	W	142.39	139.068
EA	N	42	59	E	234.58	171.607
					939.46	-0.079

Surveying - Traverse




Latitudes and Departures - Example

Side	Bearing			Length (ft.)	Latitude	Departure
	degree	minutes				
AB	S	6	15	W	189.53	-188.403
BC	S	29	38	E	175.18	-152.268
CD	N	81	18	W	197.78	29.916
DE	N	12	24	W	142.39	139.068
EA	N	42	59	E	234.58	171.607
					939.46	-0.079


$$E_{closure} = \sqrt{(E_L)^2 + (E_D)^2} = \sqrt{(-0.079)^2 + (-0.163)^2} = 0.182 \text{ ft.}$$

$$\text{Precision} = \frac{E_{closure}}{\text{perimeter}} = \frac{0.182 \text{ ft.}}{939.46 \text{ ft.}} = \frac{1}{5,176}$$


Surveying - Traverse



Group Example Problem 1




Surveying - Traverse



Group Example Problem 1


Side	Bearing			Length (ft.)	Latitude	Departure
	degree	minutes				
AB	S	77	10	E	651.2	
BC	S	38	43	W	826.7	
CD	N	64	9	W	491.0	
DE	N	29	16	E	660.5	

Surveying - Traverse




Balancing Latitudes and Departures

- Balancing the latitudes and departures of a traverse attempts to obtain more probable values for the locations of the corners of the traverse
- A popular method for balancing errors is called the **compass** or the **Bowditch rule**
- The "**Bowditch rule**" as devised by Nathaniel Bowditch, surveyor, navigator and mathematician, as a proposed solution to the problem of compass traverse adjustment, which was posed in the American journal *The Analyst* in 1807.



Surveying - Traverse

Balancing Latitudes and Departures




➤ The **compass** method assumes:

- 1) angles and distances have same error
- 2) errors are accidental


➤ The rule states:

“The error in latitude (departure) of a line is to the total error in latitude (departure) as the length of the line is the perimeter of the traverse”



Surveying - Traverse

Latitudes and Departures - Example




Recall the results of our example problem

Side	Bearing			Length (ft)	Latitude	Departure
	degree	minutes				
AB	S	6	15	W	189.53	
BC	S	29	38	E	175.18	
CD	N	81	18	W	197.78	
DE	N	12	24	W	142.39	
EA	N	42	59	E	234.58	

Surveying - Traverse

Latitudes and Departures - Example





Recall the results of our example problem

Side	Bearing			Length (ft)	Latitude	Departure
	degree	minutes				
AB	S	6	15	W	189.53	-188.403
BC	S	29	38	E	175.18	-152.268
CD	N	81	18	W	197.78	29.916
DE	N	12	24	W	142.39	139.068
EA	N	42	59	E	234.58	171.607
				939.46	-0.079	-0.163

Surveying - Traverse

Balancing Latitudes and Departures

Latitude_{AB}

$$-S = -(189.53 \text{ ft.}) \cos(6^\circ 15') = -188.40 \text{ ft.}$$



$$\text{Correction in Lat}_{AB} = \frac{L_{AB}}{\text{perimeter}}$$

$$\text{Correction in Lat}_{AB} = \frac{E_L(L_{AB})}{\text{perimeter}}$$

$$\text{Correction in Lat}_{AB} = \frac{+0.079 \text{ ft.} (189.53 \text{ ft.})}{939.46 \text{ ft.}} = +0.016 \text{ ft.}$$

Surveying - Traverse

Balancing Latitudes and Departures

Departure_{AB}

$$-W = -(189.53 \text{ ft.}) \sin(6^\circ 15') = -20.63 \text{ ft.}$$

$$\text{Correction in Dep}_{AB} = \frac{L_{AB}}{\text{perimeter}}$$

$$\text{Correction in Dep}_{AB} = \frac{E_D(L_{AB})}{\text{perimeter}}$$

$$\text{Correction in Dep}_{AB} = \frac{+0.163 \text{ ft.} (189.53 \text{ ft.})}{939.46 \text{ ft.}} = +0.033 \text{ ft.}$$

Surveying - Traverse

Balancing Latitudes and Departures

Latitude_{BC}

$$-S = -(175.18 \text{ ft.}) \cos(29^\circ 38') = -152.27 \text{ ft.}$$

$$\text{Correction in Lat}_{BC} = \frac{L_{BC}}{\text{perimeter}}$$

$$\text{Correction in Lat}_{BC} = \frac{E_L(L_{BC})}{\text{perimeter}}$$

$$\text{Correction in Lat}_{BC} = \frac{+0.079 \text{ ft.}(175.18 \text{ ft.})}{939.46 \text{ ft.}} = +0.015 \text{ ft.}$$

Surveying - Traverse

Balancing Latitudes and Departures

Departure_{BC}

$$+E = (175.18 \text{ ft.}) \sin(29^\circ 38') = 86.62 \text{ ft.}$$

$$\text{Correction in Dep}_{BC} = \frac{L_{BC}}{\text{perimeter}}$$

$$\text{Correction in Dep}_{BC} = \frac{E_D(L_{BC})}{\text{perimeter}}$$

$$\text{Correction in Dep}_{BC} = \frac{+0.163 \text{ ft.}(175.18 \text{ ft.})}{939.46 \text{ ft.}} = +0.030 \text{ ft.}$$

Surveying - Traverse

Balancing Latitudes and Departures

Length (ft.)	Latitude	Departure	Corrections		Balanced	
			Latitude	Departure	Latitude	Departure
189.53	-188.403	-20.634	0.016	0.033		
175.18	-152.268	86.617	0.015	0.030		
197.78	29.916	-195.504				
142.39	139.068	-30.576				
234.58	171.607	159.933				
939.46	-0.079	-0.163				

Corrections computed on previous slides

Surveying - Traverse

Balancing Latitudes and Departures

Length (ft.)	Latitude	Departure	Corrections		Balanced	
			Latitude	Departure	Latitude	Departure
189.53	-188.403	-20.634	0.016	0.033	-188.388	-20.601
175.18	-152.268	86.617	0.015	0.030	-152.253	86.648
197.78	29.916	-195.504				
142.39	139.068	-30.576				
234.58	171.607	159.933				
939.46	-0.079	-0.163				

Corrected latitudes and departures

Surveying - Traverse

Balancing Latitudes and Departures

Length (ft.)	Latitude	Departure	Corrections		Balanced	
			Latitude	Departure	Latitude	Departure
189.53	-188.403	-20.634	0.016	0.033	-188.388	-20.601
175.18	-152.268	86.617	0.015	0.030	-152.253	86.648
197.78	29.916	-195.504	0.017	0.034	29.933	-195.470
142.39	139.068	-30.576	0.012	0.025	139.080	-30.551
234.58	171.607	159.933	0.020	0.041	171.627	159.974
939.46	-0.079	-0.163			0.000	0.000

No error in corrected latitudes and departures


Surveying - Traverse

Balancing Latitudes and Departures

Combining the latitude and departure calculations with corrections gives:

Side	Bearing degree minutes	Length (ft.)	Latitude	Departure	Corrections		Balanced	
					Latitude	Departure	Latitude	Departure
AB	S 6° 15' W	189.53	-188.403	-20.634	0.016	0.033	-188.388	-20.601
BC	S 29° 38' E	175.18	-152.268	86.617	0.015	0.030	-152.253	86.648
CD	N 81° 18' W	197.78	29.916	-195.504	0.017	0.034	29.933	-195.470
DE	N 12° 24' W	142.39	139.068	-30.576	0.012	0.025	139.080	-30.551
EA	N 42° 59' E	234.58	171.607	159.933	0.020	0.041	171.627	159.974
		939.46	-0.079	-0.163			0.000	0.000

Surveying - Traverse




Group Example Problem 2

Balance the latitudes and departures for the following traverse.


Length (ft)	Latitude	Departure	Corrections		Balanced	
			Latitude	Departure	Latitude	Departure
600.0	450.00	339.00				
450.0	-285.00	259.50				
750.0	-164.46	-599.22				
1800.0	0.54	-0.72				

Surveying - Traverse




Group Example Problem 3

In the survey of your assign site in Project #3, you will have to balance data collected in the following form:



Surveying - Traverse



Group Example Problem 3


In the survey of your assign site in Project #3, you will have to balance data collected in the following form:

Side	Bearing degree minutes	Length (ft.)	Latitude	Departure	Corrections		Balanced	
					Latitude	Departure	Latitude	Departure
AB	N 69 53 E	713.93						
BC		606.06						
CD		391.27						
DA		781.18						

Enclosure = ft.

Precision =


Surveying - Traverse




Calculating Traverse Area

- The best-known procedure for calculating land areas is the **double meridian distance (DMD)** method
- The **meridian distance** of a line is the east-west distance from the midpoint of the line to the reference meridian
- The **meridian distance** is positive (+) to the east and negative (-) to the west


Surveying - Traverse



Calculating Traverse Area



Surveying - Traverse



Calculating Traverse Area

- The most westerly and easterly points of a traverse may be found using the departures of the traverse
- Begin by establishing an arbitrary reference line and using the departure values of each point in the traverse to determine the far westerly point

Surveying - Traverse

Calculating Traverse Area

Length (ft.)	Latitude	Departure	Corrections		Balanced	
			Latitude	Departure	Latitude	Departure
189.53	-188.403	-20.634	0.016	0.033	-188.388	-20.601
175.18	-152.268	86.617	0.015	0.030	-152.253	86.648
197.78	29.916	-195.504	0.017	0.034	29.933	-195.470
142.39	139.868	-30.576	0.012	0.025	139.900	-30.551
234.58	171.607	159.933	0.020	0.041	171.627	159.974
939.46	-0.079	-0.163			0.000	0.000

Surveying - Traverse

Calculating Traverse Area

Surveying - Traverse

DMD Calculations

The meridian distance of line EA is:

DMD of line EA is the departure of line

Surveying - Traverse

DMD Calculations

- The meridian distance of line AB is equal to:
 - the meridian distance of EA
 - + 1/2 the departure of line EA
 - + 1/2 departure of AB
- The DMD of line AB is twice the meridian distance of line AB:
 - double meridian distance of EA
 - + the departure of line EA
 - + departure of AB

Surveying - Traverse

DMD Calculations

The DMD of any side is equal to:

the DMD of the last side
+ the departure of the last side
+ the departure of the present side

$$DMD_{AB} = DMD_{EA} + dep_{EA} + dep_{AB}$$

Surveying - Traverse

DMD Calculations

Side	Balanced		DMD
	Latitude	Departure	
AB	-188.388	-20.601	-20.601
BC	-152.253	86.648	
CD	29.933	-195.470	
DE	139.080	-30.551	
EA	171.627	159.974	

The DMD of line AB is departure of line AB

Surveying - Traverse

DMD Calculations

Side	Balanced		DMD
	Latitude	Departure	
AB	-188.388	-20.601	-20.601
BC	-152.253	86.648	45.447
CD	29.933	-195.470	
DE	139.080	-30.551	
EA	171.627	159.974	

The **DMD** of line BC is DMD of line AB + departure of line AB + the departure of line BC

Surveying - Traverse

DMD Calculations

Side	Balanced		DMD
	Latitude	Departure	
AB	-188.388	-20.601	-20.601
BC	-152.253	86.648	45.447
CD	29.933	-195.470	-63.375
DE	139.080	-30.551	
EA	171.627	159.974	

The **DMD** of line CD is DMD of line BC + departure of line BC + the departure of line CD

Surveying - Traverse

DMD Calculations

Side	Balanced		DMD
	Latitude	Departure	
AB	-188.388	-20.601	-20.601
BC	-152.253	86.648	45.447
CD	29.933	-195.470	-63.375
DE	139.080	-30.551	-289.397
EA	171.627	159.974	

The **DMD** of line DE is DMD of line CD + departure of line CD + the departure of line DE

Surveying - Traverse

DMD Calculations

Side	Balanced		DMD
	Latitude	Departure	
AB	-188.388	-20.601	-20.601
BC	-152.253	86.648	45.447
CD	29.933	-195.470	-63.375
DE	139.080	-30.551	-289.397
EA	171.627	159.974	-159.974

The **DMD** of line EA is DMD of line DE + departure of line DE + the departure of line EA

Surveying - Traverse

DMD Calculations

Side	Balanced		DMD
	Latitude	Departure	
AB	-188.388	-20.601	-20.601
BC	-152.253	86.648	45.447
CD	29.933	-195.470	-63.375
DE	139.080	-30.551	-289.397
EA	171.627	159.974	-159.974

Notice that the **DMD** values can be positive or negative

Surveying - Traverse

Traverse Area - Double Area

➤ The sum of the products of each points DMD and latitude equal twice the area, or the **double area**

Side	Balanced		DMD	Double Areas
	Latitude	Departure		
AB	-188.388	-20.601	-20.601	3,881
BC	-152.253	86.648	45.447	
CD	29.933	-195.470	-63.375	
DE	139.080	-30.551	-289.397	
EA	171.627	159.974	-159.974	

➤ The double area for line AB equals **DMD** of line AB times the latitude of line AB

Surveying - Traverse

Traverse Area - Double Area

➤ The sum of the products of each points DMD and latitude equal twice the area, or the double area

Side	Balanced		DMD	Double Areas
	Latitude	Departure		
AB	-188.388	-20.601	-20.601	3,881
BC	-152.253	86.648	45.447	-6,919
CD	29.933	-195.470	-63.375	-1,897
DE	139.080	-30.551	-289.397	-40,249
EA	171.627	159.974	-159.974	-27,456

➤ The double area for line BC equals DMD of line BC times the latitude of line BC

Surveying - Traverse

Traverse Area - Double Area

➤ The sum of the products of each points DMD and latitude equal twice the area, or the double area

Side	Balanced		DMD	Double Areas
	Latitude	Departure		
AB	-188.388	-20.601	-20.601	3,881
BC	-152.253	86.648	45.447	-6,919
CD	29.933	-195.470	-63.375	-1,897
DE	139.080	-30.551	-289.397	-40,249
EA	171.627	159.974	-159.974	-27,456

➤ The double area for line CD equals DMD of line CD times the latitude of line CD

Surveying - Traverse

Traverse Area - Double Area

➤ The sum of the products of each points DMD and latitude equal twice the area, or the double area

Side	Balanced		DMD	Double Areas
	Latitude	Departure		
AB	-188.388	-20.601	-20.601	3,881
BC	-152.253	86.648	45.447	-6,919
CD	29.933	-195.470	-63.375	-1,897
DE	139.080	-30.551	-289.397	-40,249
EA	171.627	159.974	-159.974	-27,456

➤ The double area for line DE equals DMD of line DE times the latitude of line DE

Surveying - Traverse

Traverse Area - Double Area

➤ The sum of the products of each points DMD and latitude equal twice the area, or the double area

Side	Balanced		DMD	Double Areas
	Latitude	Departure		
AB	-188.388	-20.601	-20.601	3,881
BC	-152.253	86.648	45.447	-6,919
CD	29.933	-195.470	-63.375	-1,897
DE	139.080	-30.551	-289.397	-40,249
EA	171.627	159.974	-159.974	-27,456

➤ The double area for line EA equals DMD of line EA times the latitude of line EA

Surveying - Traverse

Traverse Area - Double Area

➤ The sum of the products of each points DMD and latitude equal twice the area, or the double area

Side	Balanced		DMD	Double Areas
	Latitude	Departure		
AB	-188.388	-20.601	-20.601	3,881
BC	-152.253	86.648	45.447	-6,919
CD	29.933	-195.470	-63.375	-1,897
DE	139.080	-30.551	-289.397	-40,249
EA	171.627	159.974	-159.974	-27,456

1 acre = 43,560 ft.²


Surveying - Traverse

Traverse Area - Double Area

➤ The sum of the products of each points DMD and latitude equal twice the area, or the double area

Side	Balanced		DMD	Double Areas
	Latitude	Departure		
AB	-188.388	-20.601	-20.601	3,881
BC	-152.253	86.648	45.447	-6,919
CD	29.933	-195.470	-63.375	-1,897
DE	139.080	-30.551	-289.397	-40,249
EA	171.627	159.974	-159.974	-27,456
2 Area =				-72,641
1 acre = 43,560 ft. ²				Area = 0.834 acre


Surveying - Traverse



Traverse Area - Double Area

- The word "acre" is derived from Old English *æcer* (originally meaning "open field", cognate to Swedish "åker", German *acker*, Latin *ager* and Greek *αγρος* (*agros*)).
- The acre was selected as approximately the amount of land tillable by one man behind an ox in one day.
- This explains one definition as the area of a rectangle with sides of length one chain (66 ft.) and one furlong (ten chains or 660 ft.).


Surveying - Traverse



Traverse Area - Double Area


- The word "acre" is derived from Old English *æcer* (originally meaning "open field", cognate to Swedish "åker", German *acker*, Latin *ager* and Greek *αγρος* (*agros*)).
- A long narrow strip of land is more efficient to plough than a square plot, since the plough does not have to be turned so often.
- The word "furlong" itself derives from the fact that it is *one furrow long*.

Surveying - Traverse




Traverse Area - Double Area

- The word "acre" is derived from Old English *æcer* (originally meaning "open field", cognate to Swedish "åker", German *acker*, Latin *ager* and Greek *αγρος* (*agros*)).



Surveying - Traverse



Traverse Area – Example 4

- Find the area enclosed by the following traverse


Side	Balanced		DMD	Double Areas
	Latitude	Departure		
AB	600.0	200.0		
BC	100.0	400.0		
CD	0.0	100.0		
DE	-400.0	-300.0		
EA	-300.0	-400.0		

2 Area =

1 acre = 43,560 ft.²

Area = ft.²
 acre


Surveying - Traverse



DPD Calculations

- The same procedure used for DMD can be used the **double parallel distances (DPD)** are multiplied by the balanced departures
- The **parallel distance** of a line is the distance from the midpoint of the line to the reference parallel or east–west line


Surveying - Traverse



Rectangular Coordinates


- Rectangular coordinates are the convenient method available for describing the horizontal position of survey points
- With the application of computers, rectangular coordinates are used frequently in engineering projects
- In the US, the **x-axis** corresponds to the east–west direction and the **y-axis** to the north–south direction

Surveying - Traverse



Rectangular Coordinates Example

In this example, the length of AB is 300 ft. and bearing is shown in the figure below. Determine the coordinates of point B



Latitude_{AB} = 300 ft. cos(42°30') = 221.183 ft.


Departure_{AB} = 300 ft. sin(42°30') = 202.677 ft.

$x_B = 200 + 202.667 = 402.667$ ft.

$y_B = 300 + 221.183 = 521.183$ ft.


Coordinates of Point A (200, 300)

Surveying - Traverse



Rectangular Coordinates Example

In this example, it is assumed that the coordinates of points A and B are known and we want to calculate the latitude and departure for line AB




Latitude_{AB} = $y_B - y_A$
Latitude_{AB} = -400 ft.

Departure_{AB} = $x_B - x_A$
Departure_{AB} = 220 ft.

Coordinates of Point A (100, 300)


Coordinates of Point B (320, -100)

Surveying - Traverse




Rectangular Coordinates Example

Consider our previous example, determine the x and y coordinates of all the points



Side	Balanced	
	Latitude	Departure
AB	-188.388	-20.601
BC	-152.253	86.648
CD	29.933	-195.470
DE	139.080	-30.551
EA	171.627	159.974

Surveying - Traverse



Rectangular Coordinates Example

➤ x coordinates

E = 0 ft.

A = E + 159.974 = 159.974 ft.

B = A - 20.601 = 139.373 ft.


C = B + 86.648 = 226.021 ft.

D = C - 195.470 = 30.551 ft.

E = D - 30.551 = 0 ft.

Side	Balanced	
	Latitude	Departure
AB	-188.388	-20.601
BC	-152.253	86.648
CD	29.933	-195.470
DE	139.080	-30.551
EA	171.627	159.974

Surveying - Traverse



Rectangular Coordinates Example

➤ y coordinates

C = 0 ft.

D = C + 29.933 ft.

E = D + 139.080 = 169.013 ft.


A = E + 171.627 = 340.640 ft.

B = A - 188.388 = 152.252 ft.


C = B - 152.252 = 0 ft.

Side	Balanced	
	Latitude	Departure
AB	-188.388	-20.601
BC	-152.253	86.648
CD	29.933	-195.470
DE	139.080	-30.551
EA	171.627	159.974


Surveying - Traverse



Rectangular Coordinates Example



Surveying - Traverse




Group Example Problem 5

Compute the x and y coordinates from the following balanced.

Side	Bearing degree minutes	Length (ft)	Latitude	Departure	Balanced		Points	Coordinates	
					Latitude	Departure		x	y
AB	S 6 15 W	189.53	-188.403	-20.634	-188.388	-20.601	A	100.000	100.000
BC	S 29 38 E	175.18	-152.268	86.617	-152.253	86.646	B		
CD	N 81 18 W	197.78	29.916	-195.504	29.933	-195.470	C		
DE	N 12 24 W	142.39	139.068	-30.576	139.090	-30.551	D		
EA	N 42 59 E	234.58	171.607	159.393	171.627	159.374	E		
			939.46	-0.079	-0.163	0.000	A		

Surveying - Traverse




Area Computed by Coordinates


The area of a traverse can be computed by taking each y coordinate multiplied by the difference in the two adjacent x coordinates

(using a sign convention of + for next side and - for last side)

Surveying - Traverse



Area Computed by Coordinates



Twice the area equals:

$$= 340.640(139.373 - 0.0)$$

$$+ 152.253(226.020 - 159.974)$$

$$+ 0.0(30.551 - 139.373)$$


$$+ 29.933(0.0 - 226.020)$$

$$+ 169.013(159.974 - 30.551)$$

$$= 72,640.433 \text{ ft.}^2$$


Area = 0.853 acre Area = 36,320.2 ft.²

Surveying - Traverse



Area Computed by Coordinates

There is a simple variation of the coordinate method for area computation




Twice the area equals:

$$= X_1Y_2 + X_2Y_3 + X_3Y_4 + X_4Y_5 + X_5Y_1$$


$$- X_2Y_1 - X_3Y_2 - X_4Y_3 - X_5Y_4 - X_1Y_5$$

Surveying - Traverse



Area Computed by Coordinates

There is a simple variation of the coordinate method for area computation



Twice the area equals:

$$159.974(152.253) + 139.373(0.0) + 226.020(29.933) + 30.551(169.013) + 0.0(340.640)$$


$$- 340.640(139.373) - 152.253(226.020)$$

$$- 0.0(30.551) - 29.933(0.0) - 169.013(159.974)$$

$$= -72,640 \text{ ft.}^2$$

Area = 36,320 ft.²

End of Surveying - Traverse



Any Questions?




Table of Survey Data

Line	Bearing	Distance
(A) to (B)	S 6 15 W	189.53
(B) to (C)	S 29 38 E	175.18
(C) to (D)	N 81 18 W	197.78
(D) to (E)	N 12 24 W	142.39
(E) to (A)	N 42 59 E	234.58
(A) to (B)	S 6 15 W	189.53