

2021 DRAG TIRE GUIDE



www.racegoodyear.com

Drag Tire Compound Data

Compound	Primary Application Vehicle
D-8	High grip compound for high horsepower radial tire applications
D-2A	High grip compound used for TAD and some bracket applications
D-2G	For Pro Mod and TAFC. High level of grip that can also sustain wheelspeed
D-2H	For TF/FC and other high horsepower applications
D-1	For use on dragsters and other lightweight cars
D-4B	For Stock Eliminator and slightly more tractive than D-4A
D-4A	Good for hot or slick track conditions
D-4	Excellent wear/longevity for heavy applications, +3,000 lbs.
D-1B	New and improved compound for Stock and Factory Stock Showdown
D-1A	For use on Stock and Super Stock Radials
D-6	Works well on Dragsters and 1,500 - 2,500 lbs. cars
D-5	Works well on Dragsters and 2,000 - 3,200 lbs. cars
D-7	Limited application compound. Designed to eliminate shake
D-3	For heavy manual and automatic cars
HARD	Frontrunners

Listed in order from softest to hardest

Note that in some cases, a softer compound is not necessarily more tractive due to the nature of Goodyear's drag race compounds.



Top Fuel & Funny Car

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
231233	2747	D-2H	36.0x17.5-16	16	36.6	21.8	17.3	48.0	115.0	\$ 919.00	BL, LW

Pro Mod, Alcohol, Pro Stock

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
229258	3122	D-2G	34.5x17.0-16	16	34.8	21.3	17.0	43.0	109.00	\$ 558.00	
233411	2433	D-4A	33.5x17.0-16	16	33.4	21.5	17.7	43.0	105.00	\$ 667.00	BL, SS
243701	2739	D-2H	35.0x17.0-16	16	35.2	19.6	17.0	49	110.00	\$ 509.00	NEW FOR 2021
230874	2912		Shield							\$ 173.00	

Factory Stock

240012	4902	D-1A	30.0x9.0-15	9	29.6	12.4	9.8	21.5	93.1	\$ 299.00	R
240059	4904	D-1A	30.0x9.0-15	9	30.1	12.8	9.8	21.7	94.7	\$ 299.00	R

Western Region

Carroll Shelby Enterprises, Inc.
Las Vegas, Nevada
Phone - 702.430.5160
www.carrollshelbyent.com

Central Region

Carter-Maxwell, Inc.
Bethany, Oklahoma
Phone - 405.789.8253

Eastern Region

Shelby Carter Maxwell, Inc.
High Point, North Carolina
Phone - 336.884.0328

Canada

Fairchild Race Tire
Fenwick, Ontario
Phone - +1.905.641.8633
www.fcracetires.com

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: R - Radial, HG - High Growth, LW - Lightweight, MS - Medium stiff sidewall, SS - Stiff sidewall

ET - Extended tread life, BL - Bead lock wheel required



Stock, Super Stock

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
210598	2790	D-5	28.0x9.0-15	8	28.0	10.7	9.0	21.3	88.0	\$ 221.00	
210599	2791	D-5	28.0x10.0-15	10	28.0	12.0	10.0	23.1	88.0	\$ 226.00	
210596	2796	D-5	29.0x11.0-15	10	29.0	12.8	10.9	25.1	91.0	\$ 262.00	
210597	2797	D-5	29.0x12.0-15	11	29.0	13.9	11.8	25.1	91.0	\$ 269.00	
219253	4915	D-8	30.0x10.5-15	10	29.6	13.3	10.5	23.5	93.0	\$ 294.00	R
23623	1909	D-5	30.0x9.0-15	8	30.7	12.4	9.0	25.0	96.5	\$ 290.00	
190161	2018	D-5	31.0x13.0-15	12	30.6	15.6	12.8	33.4	96.0	\$ 374.00	MS
219043	4909	D-8	31.0x13.5-15	14	31.7	16.9	13.8	33.0	99.5	\$ 347.00	R
190162	2019	D-5	31.0x14.0-15	12	31.0	16.2	14.0	35.8	97.0	\$ 378.00	MS
237741	4917	D-8	31.0x16.0-15	15	31.0	19.4	16.3	37.3	101.0	\$ 398.00	R
23556	1984	D-5	32.0x14.0-15	14	32.4	17.0	14.4	39.3	101.0	\$ 370.00	PRICE REDUCTION
23540	1672	D-5	32.0x14.5-15	14	32.8	17.7	14.8	39.4	103.0	\$ 362.00	PRICE REDUCTION - MS
220522	4463	D-8	33.0x14.5-15	14	33	17.4	14.5	36.4	103.0	\$ 387.00	
190163	2070	D-6	33.0x14.5-15	14	32.8	18.9	14.9	34.1	104.0	\$ 399.00	
236033	4892	D-1A	30.0x9.0-15	9	29.5	11.8	9.1	21.1	92.5	\$ 293.00	R, LW
243651	5192	D-1B	30.0x9.0-15	9	29.5	11.8	9.1	21.1	92.5	\$ 293.00	NEW FOR 2021 -R, LW
236035	4894	D-1A	30.0x9.0-15	9	30.0	12.0	9.1	21.4	94.0	\$ 293.00	R, LW

Western Region
 Carrol Shelby Enterprises, Inc.
 Las Vegas, Nevada
 Phone - 702.430.5160
www.carrollshelbyent.com

Central Region
 Carter-Maxwell, Inc.
 Bethany, Oklahoma
 Phone - 405.789.8253

Eastern Region
 Shelby Carter Maxwell, Inc.
 High Point, North Carolina
 Phone - 336.884.0328

Canada
 Fairchild Race Tire
 Fenwick, Ontario
 Phone - +1.905.641.8633
www.fcracetires.com

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: R - Radial, HG - High Growth, LW - Lightweight, MS - Medium stiff sidewall, SS - Stiff sidewall

ET - Extended tread life, BL - Bead lock wheel required

www.racegoodyear.com



Super Gas

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
23556	1984	D-5	32.0x14.0-15	14	32.4	17.0	14.4	39.3	101	\$ 370.00	PRICE REDUCTION
23540	1672	D-5	32.0x14.5-15	14	32.8	17.7	14.8	39.4	103	\$ 362.00	PRICE REDUCTION - MS
23558	1408	D-5	32.0x16.0-15	15	32.4	18.4	16.0	39.6	102	\$ 382.00	PRICE REDUCTION - MS
190102	2051	D-4A	32.5x17.0-15	15	32.5	20.8	17.2	41.1	100	\$ 464.00	
192212	2078	D-5	33.0x15.0-15	14	33.2	17.5	15.0	40.6	104	\$ 407.00	MS
190167	2052	D-6	33.0x16.0-15	15	32.8	19.6	16.1	38.0	102	\$ 382.00	PRICE REDUCTION
191202	2053	D-4A	33.0x17.0-15	15	32.8	20.6	17.3	42.9	102	\$ 464.00	SS
233411	2433	D-4A	33.5x17.0-16	16	33.4	21.5	17.7	43.0	105	\$ 667.00	BL, SS
228522	2211	D-4A	33.5x17.0-16	16	33.4	21.2	17.5	42.5	105	\$ 460.00	BL, SS
227639	2775	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	40.3	105	\$ 422.00	PRICE REDUCTION - BL
235137	2776	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	45.1	105	\$ 423.00	PRICE REDUCTION - BL, SS

Top Dragster, Top Sportsman

242495	2719	D-2H	35.0x15.0-16	16	35	18.8	14.8	42.0	110	\$ 461.00	NEW FOR 2021
235137	2776	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	45.1	105	\$ 423.00	PRICE REDUCTION - BL, SS
243701	2739	D-2H	35.0x17.0-16	16	35.2	19.6	17.0	49	110.00	\$ 509.00	NEW FOR 2021

Western Region
 Carrol Shelby Enterprises, Inc.
 Las Vegas, Nevada
 Phone - 702.430.5160
www.carrollshelbyent.com

Central Region
 Carter-Maxwell, Inc.
 Bethany, Oklahoma
 Phone - 405.789.8253

Eastern Region
 Shelby Carter Maxwell, Inc.
 High Point, North Carolina
 Phone - 336.884.0328

Canada
 Fairchild Race Tire
 Fenwick, Ontario
 Phone - +1.905.641.8633
www.fcracetires.com

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: R - Radial, HG - High Growth, LW - Lightweight, MS - Medium stiff sidewall, SS - Stiff sidewall

ET - Extended tread life, BL - Bead lock wheel required



Frontrunner

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
177193	1445	HARD	22.0x2.5-17	2.5	22.0	2.5	1.5	4.5	69.9	\$ 182.00	PRICE REDUCTION - ET
215560	2904	HARD	22.0x4.0-17	2.5	22.9	3.4	3.1	5.2	72	\$ 274.00	
240982	2989	HARD	23.0x5.0-15	4	23.0	6.8	5.0	12.2	72.7	\$ 242.00	
189891	1961	HARD	23.0x5.0-15	4	23.0	6.8	5.0	12.7	72.7	\$ 201.00	PRICE REDUCTION
189955	1962	HARD	24.0x5.0-15	4	24.0	6.8	5.0	11.3	75.8	\$ 191.00	PRICE REDUCTION
215499	2991	HARD	25.0x4.5-15	4	25.0	6.5	4.5	11.6	78.5	\$ 209.00	LW
190130	1964	HARD	26.0x4.5-15	4	26.0	6.3	4.5	10.8	81.2	\$ 196.00	PRICE REDUCTION
197495	1965	HARD	27.0x4.5-15	4	27.0	7.9	4.5	13.5	84.8	\$ 197.00	PRICE REDUCTION
189822	1966	HARD	28.0x4.5-15	4	28.0	7.7	5.1	12.4	89.1	\$ 198.00	PRICE REDUCTION

Western Region
 Carrol Shelby Enterprises, Inc.
 Las Vegas, Nevada
 Phone - 702.430.5160
www.carrollshelbyent.com

Central Region
 Carter-Maxwell, Inc.
 Bethany, Oklahoma
 Phone - 405.789.8253

Eastern Region
 Shelby Carter Maxwell, Inc.
 High Point, North Carolina
 Phone - 336.884.0328

Canada
 Fairchild Race Tire
 Fenwick, Ontario
 Phone - +1.905.641.8633
www.fcracetires.com

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***
 Comments: R - Radial, HG - High Growth, LW - Lightweight, MS - Medium stiff sidewall, SS - Stiff sidewall
 ET - Extended tread life, BL - Bead lock wheel required



Comp Eliminator, Super Comp

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
23653	2976	D-6	26.0x8.0-15	9	26.4	10.5	8.9	16.0	83	\$ 200.00	LW
206637	2585	D-3	31.0x12.0-15	12	30.8	15.2	12.0	22.6	96.5	\$ 382.00	
219042	4911	D-8	32.0x14.0-15	14	32.1	17.2	13.8	32.4	101	\$ 376.00	R
193992	1911	D-1	32.0x14.5-15	14	32.2	17.7	15.0	34.1	101	\$ 401.00	
190102	2051	D-4A	32.5x17.0-15	15	32.5	20.8	17.2	41.1	100	\$ 464.00	LW, SS
23654	1288	D-7	33.0x12.0-15	12	32.4	16.5	12.3	28.8	102	\$ 394.00	HG
190163	2070	D-6	33.0x14.5-15	14	32.8	18.9	14.9	34.1	104	\$ 399.00	
215174	2533	D-2A	33.0x16.0-15	15	32.4	19.9	16.3	39.6	106	\$ 379.00	
190167	2052	D-6	33.0x16.0-15	15	32.8	19.6	16.1	38.0	102	\$ 382.00	
215232	2534	D-2A	33.0x17.0-15	15	32.4	20.5	17.4	39.5	104	\$ 391.00	
227639	2775	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	40.3	105	\$ 422.00	PRICE REDUCTION-BL
235137	2776	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	45.1	105	\$ 423.00	PRICE REDUCTION-BL
242495	2719	D-2H	35.0x15.0-16	16	35	18.8	14.8	42.0	110	\$ 461.00	NEW FOR 2021

Western Region
 Carrol Shelby Enterprises, Inc.
 Las Vegas, Nevada
 Phone - 702.430.5160
www.carrollshelbyent.com

Central Region
 Carter-Maxwell, Inc.
 Bethany, Oklahoma
 Phone - 405.789.8253

Eastern Region
 Shelby Carter Maxwell, Inc.
 High Point, North Carolina
 Phone - 336.884.0328

Canada
 Fairchild Race Tire
 Fenwick, Ontario
 Phone - +1.905.641.8633
www.fcracetires.com

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: R - Radial, HG - High Growth, LW - Lightweight, MS - Medium stiff sidewall, SS - Stiff sidewall

ET - Extended tread life, BL - Bead lock wheel required



Landspeed

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
215560	2904	HARD	22.0x4.0-17	2.5	22.9	3.4	3.1	5.2	72	\$ 274.00	
234517	2952	HARD	21.0x5.0-15	4.5	21.3	5.4	4.1	10.0	68.5	\$ 640.00	
234515	2953	HARD	23.0x5.0-15	4.5	23.1	7.0	5.0	12.0	74.2	\$ 664.00	
234514	2954	HARD	25.0x4.5-15	4.5	24.8	6.7	4.0	12.0	79.0	\$ 670.00	
234516	2956	HARD	28.0x4.5-15	4.5	27.8	7.7	4.5	13.0	88.4	\$ 699.00	
225063	2934	HARD	28.0x10.0-15	9.5	28.3	13.6	10.0	22.0	89.0	\$ 235.00	
239857	2860	HARD	24.5x7.5-16	5.5	24.5	7.4	5.5	14.2	78.5	\$ 711.00	LW
233188	2870	HARD	30.0x9.0-18	6.5	30.0	8.5	3.0	16.5	93.0	\$ 742.00	LW

D Number	Min. PSI	Max Load	Max Speed
2904	90 psi	1200 lbs.	300 mph
2952	50 psi	1200 lbs.	300 mph
2953	70 psi	1700 lbs.	300 mph
2954	70 psi	1700 lbs.	300 mph
2956	70 psi	1700 lbs.	300 mph
2934	70 psi	1700 lbs.	300 mph
2860	70 psi	2300 lbs.	320 mph
2870	70 psi	2300 lbs.	320 mph

Western Region
 Carrol Shelby Enterprises, Inc.
 Las Vegas, Nevada
 Phone - 702.430.5160
www.carrollshelbyent.com

Central Region
 Carter-Maxwell, Inc.
 Bethany, Oklahoma
 Phone - 405.789.8253

Eastern Region
 Shelby Carter Maxwell, Inc.
 High Point, North Carolina
 Phone - 336.884.0328

Canada
 Fairchild Race Tire
 Fenwick, Ontario
 Phone - +1.905.641.8633
www.fcracetires.com

*** Rim width tolerance is plus or minus one inch from specified Rim Width ***

Comments: R - Radial, HG - High Growth, LW - Lightweight, MS - Medium stiff sidewall, SS - Stiff sidewall

ET - Extended tread life, BL - Bead lock wheel required

www.racegoodyear.com