

Qualideck®









KEY REASONS TO SPECIFY QUALIDECK®

EXPERIENCED 30+ years manufacturing polyurethane coatings

PROVEN: Over 50 million square feet installed with zero failures

SAFE: Low VOCs, solvent free, contains no TDI, UL certified UL 723 & UL 790

DURABLE: Withstanding the test of time

2.5 million SF Toronto Airport garage (17+ years in service)

US Embassy, Canada (15+ years in service) AT&T, Chicago (23+ years in service)

QUALITY ASSURANCE: ISO 9001 + 14001

FASTER:

Faster cure rate vs. competitive products

WARRANTIES: Most competitive in the industry

5 Year Manufacturer's Warranty 5+5 Year Manufacturer's Warranty

5 Year Joint + Several-Certified Qualideck® Applicators Only 10 Year-See rep for details


MADE IN USA: Supports American jobs ENVIRONMENTAL: LEED credits available

CERTIFIED: Approved/certified applicators assure quality at all levels

SUPERIOR PERFORMANCE

FEATURES & BENEFITS

- Topcoat (4200 PSI, D412)
 Longer wearing, holds aggregate better and longer
- Membrane elongation (1103%, D412)
 Prevents cracking through the topcoat




QUICK REFERENCE

Testing Data	Description	Primer	Membrane	Top Coat	Systems
ASTM D7234	Adhesion to Substrate	•	•		•
ASTM D412	Tensile/Elongation			•	
ASTM D1640	Cure Rate		•	•	
ASTM D2240	Hardness				
ASTM D573	Heat Resistance Tensile/Elongation				
ASTM D3137	Hydrolytic Stability Tensile/Elongation				
ASTM D471/D412	Water Absorption				
ASTM D903	Conc Adhesion				
WPC TT-3	Intercoat Adhesion			•	
ASTM C957	Chemical Resistance				
ASTM C1371	Thermal Emittance			•	
ASTM C1549	Solar Reflectance				
ASTM E1980	Solar Reflectance Index				
ASTM D2792	Solvent & Fuel Resistance				
ASTM C501	Abrasion Resistance				
ASTM D1149	Ozone Resistance				
ASTM D822/G53/D412	Weather Resistance				
ASTM D1004	Tear Resistance				
ASTM E96	Moisture Vapor Transmission				
WPC TT-4/ASTM CP57	Crack Bridging				
ASTM D4541	Pull Off Adhesion				
WPC TT-5/ASTM X501	Wear Resistance				
ASTM C1028	Skid Resistance				
ASTM C1202	Rapid Chloride Permeability				

ALL QUALIDECK® PRODUCTS ARE LOW VOC AND ARE COMPLIANT WITH CALIFORNIA'S VOC REGULATIONS (<50g/L)

PERFORMANCE BY DESIGN





Qualideck[®]

Qualideck® Traffic Bearing Membrane							
System	Medium Duty	Heavy Duty	Extra Heavy Duty	Extreme Duty			
Primer Q152	4 mils	4 mils	4 mils	4 mils			
Membrane 0252	25 mils	25 mils	25 mils	25 mils			
Intermediate / Top Coat 0372 (Aromatic)	*15 mils	15 mils / 15 mils	25 mils / 15 mils	30 mils / 20 mils			
UV Top Coat Q582 (Aliphatic)	*15 mils	15 mils	15 mils	20 mils			
Sand Aggregate	10–15lbs / 100sf/ Coat	10–15lbs / 100sf / Coat	10–15lbs / 100sf/ Coat	10–15lbs / 100sf/ Coat			
Total	*40 mils	55 mils	65 mils	75 mils			

^{*}NOTE: Use UV Q582 for full sun exposure or Q372 aromatic for non sun exposure

APT AMERICAS — >>> — APT ASIA PACIFIC

World Headquarters 109 Conica Lane, PO Box 160 Harmony, PA 16037 USA

Tel. (724) 452-1330 Fax. (724) 452-1703 Toll Free (888) 266-4221

Factory 3 Dunlopillo Drive Dandenong Victoria 3175 Australia

Tel. +61 3 8792 8000 Fax. +61 3 8792 8001





APT – an ISO 9001 & 14001 certified company

www.qualideck.com

APT warrants its products to be free of manufacturing defects and to meet published physical properties when applied, cured, and tested in accordance with ASTM and APT standards. This warranty is in lieu of all warranties expressed or implied including any warranty of merchantability or fitness for a particular purpose in connection with this product. Neither seller nor supplier shall be liable for any loss or damage either direct, incidental or consequential regardless of legal theory asserted, including negligence, merchantability and/or strict liability. Seller's and Supplier's obligation shall be to replace such quantity of product proven to be defective. Before using, user shall determine suitability of product for his intended use and user assumes all risk in connection therewith.