

# Regulated AC Power Adapter 12V DC / 3A

pro-ELEC

RoHS  
Compliant



## Input Characteristics

Rated Voltage	: 100 – 240V AC
Variation Range	: 90 – 264V AC
Rated Frequency	: 50/60Hz
Variation Frequency	: 47 – 63Hz
Input Current	: 1.2A Max. @ Any input AC voltage & output full load
Inrush Current	: 60A Max. Cold start @ 240V AC input, rated output load & 25°C ambient
AC Leakage Current	: 0.25mA Max. @ 240V AC input

## Output Characteristics

Voltage	Min. Load	Rated Load	Output Power
12V DC	0.01A	3A	36W

## Combined Load / Line Regulation

Voltage	Min. Load	Rated Load	Line Regulation	Load Regulation
12V DC	0.01A	3A	± 1%	± 5%

<b>Ripple and Noise</b>	: Under normal voltage & nominal load, the ripple & noise are as follows when measure with Max. Bandwidth of 20MHz & parallel 10 $\mu$ F electrolysis capacitor & 0.1 $\mu$ F ceramic capacitor crossed connect at testing point. Voltage: +12V DC Ripple & Noise (Max.): 120mVp-p
Turn on Delay Time	: 2S Max. @ 115V AC input and output Max. Load
Rise Time	: 40mS Max. @ 115V AC input and output Max. Load
Hold Up Time	: 5mS Min. @ 115V AC input and output Max. Load
Efficiency	: Average efficiency 87.4% minimum @ 25%, 50%, 75% & 100% of full-loading and 230V AC input (After warm up 30 minutes). Meet with Energy star level VI. No load input watt $\leq$ 0.1W
Overshoot	: 10% Max. When power supply @ turn on or turn off.

## Environmental Requirement

Operating Temperature	: 0°C to 40°C, Full load, Normal Operation
Storage Temperature	: -40°C to 85°C
Relative Humidity	: 5% (0°C) ~ 95% (40°C) RH, 72Hrs, Full load, Normal operating

## Mechanical Requirement

Enclosure	: 110mm (L) $\times$ 52mm (W) $\times$ 33mm (H)
Input Connector	: 2 Pin Input plug


## Outline Dimension

Out Cord	: UL1185 18AWG VW-1 80° 300V, FT1 Line with word on the cord Length: 1.2m.
DC Plug	: 5.5mm $\times$ 2.5mm $\times$ 12mm
AC	: 1.2m, 2 * 0.845mm <sup>2</sup>

# Regulated AC Power Adapter 12V DC / 3A

pro-ELEC

## Diagram



Dimensions : Millimetres

## Part Number Table

Description	Part Number
Regulated AC Power Adapter, 12V DC, 3A, 36W	28-19381

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-ELEC is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.farnell.com  
www.cpc.co.uk

pro-ELEC